



## INSTRUCTIONS FOR MOUNTING TIGER TRACTOR FRONT MOUNTED LAWNMOWER

- 1- ATTACH STANDARD BULLDOZER FRAME TO TRACTOR IN REGULAR MANNER AT POINTS "B" & "C".
  - 2- ATTACH MOWER TO BULLDOZER FRAME AT POINT "A".
  - 3- ATTACH THROTTLE AND CLUTCH CONTROL ASSEMBLY TO BULLDOZER FRAME AT POINT "B". ATTACH "BRACE PLATE" BEHIND DOZER EARS
  - 4- TO ENGAGE MOWER CLUTCH PULL BACK ON HAND LEVER AT POINT "D". TO DISENGAGE PUSH FORWARD.
  - 5- IF MOTOR V BELTS WEAR OR STRETCHES MOTOR CAN BE MOVED FORWARD OR BACKWARD IN ENLARGED BOLT HOLES. ADDITIONAL ADJUSTMENT POSSIBLE BY TURNING THREADED CLEVIS AT POINT "E".
- NOTE: 2 H.P. ENGINE MOUNTED ON MOWER DRIVES MOWER REEL ONLY.



TIGER TRACTOR CORPORATION  
KEYSER, WEST VIRGINIA