



DETAIL SHOWING HOW BRAKE-MOUNTING-PLATE IS ATTACHED TO TRACTOR FRAME.

POSITION PLATE SO THAT HOLE "A" IS AROUND REAR AXLE WITH LONG PORTION OF PLATE TOWARD REAR OF TRACTOR

WELD OR SPOT AND DRILL HOLES IN TRACTOR FRAME AT POINTS "B" & "C", BOLT PLATE TO FRAME AT THESE POINTS.

INSTRUCTIONS FOR MOUNTING "SPECIAL HOLDING BRAKE" ON 1954 TIGER TRACTOR.

- (1) - THE HOLDING BRAKE COMES AS A PREFABRICATED PACKAGE AND ALL YOU NEED DO IS MOUNT IT ON THE TRACTOR. IT IS COMPLETELY PREASSEMBLED AND READY FOR OPERATION WHEN MOUNTED.
- (2) - THE BRAKE MOUNTS OVER THE LEFT REAR AXLE AND MOUNTS FLUSH AGAINST TRACTOR FRAME. IMPORTANT: FIRST REMOVE REAR AXLE RETAINING COLLAR IMMEDIATELY ADJACENT TO AXLE SHAFT HOUSING.
- (3) - AFTER MOUNTING EITHER DRILL HOLES OR WELD TO SIDE OF TRACTOR FRAME.
- (4) - TIGHTEN SET SCREWS AFTER POSITIONING ON AXLE SHAFT.
- (5) - TO ADJUST BRAKE (I.E. TO TIGHTEN) TURN NUT AT POINT "D."